



JOINT FILLER

Suitable for filling and sealing expansion joints, cracks, splits

Storage:

Store in cool, dry conditions. Min. 12 months shelf-life in original, sealed containers. Protect containers from frost.

Surface Preparation:

The surface must be dry, clean, and free from dust and grease. Prime very absorbent surfaces with the parquet joint material thinned with water (4 parts water : 1 part Pallmann Parquet Joint Filler). Deep joints should be filled using several layers.

Application:

1. Cut off the nozzle tip at an angle and according to the desired joint width – screw onto the cartridge. Use only at temperatures above 18 – 25 °C and relative humidity below 65 %.
2. Apply the sealing compound evenly onto the surface using a suitable cartridge-gun. Distribute the compound in the joint and immediately smooth off.
3. Clean off fresh material immediately with water. Clean tools with water immediately after use.
4. The joint compound can, according to joint width, be sanded down, painted and sealed after approx. 24 hours*.

*Under normal conditions at 20 °C.



04.2010

Pallmann | A Brand of UFLOOR Systems
D | JP Coatings GmbH
Im Kreuz 6 | D-97076 Würzburg
Telefon +49 (0)931 27964-0
Telefax +49 (0)931 27964-50
E-Mail info@pallmann.net
Internet www.pallmann.net

GB | Uzin Ltd.
Canute Point - Tachbrook Park Drive |
Leamington Spa
Warwickshire-GB-CV34 6RH
Telephone: +44 (0)1926 436 700
Telefax +44 (0)1926 881 893
E-mail info@uzin.co.uk
Internet www.uzin.co.uk

NZ | AU UFLOOR Systems NZ Ltd.
PO Box 426 Whangaparaoa 0943
New Zealand
Tel: +64 9 424 0366
Fax: +64 9 424 0366 |
E-mail: ufloor-systems@xtra.co.nz



PALLMANN